

VILLAGE OF ORLAND PARK

DEPARTMENT OF DEVELOPMENT SERVICES 14700 S. Ravinia Avenue, Orland Park, IL 60462 Phone (708) 403-5300 Fax (708) 403-6215 E-Mail developmentservices@orland-park.il.us

Concrete & Paver Brick Requirements

CONCRETE

- Patios & Service Walks: Minimum 2" stone base, 4" concrete thickness.
- <u>Public Sidewalks</u>: Minimum 2" stone base. 5" concrete thickness formed with 2" x 6" forms. 6 bag mix reinforced with 6 x 6 x 10 wire or fiber mesh thru driveway.
- Garage Slab: Minimum 2" stone base. 5" concrete thickness unreinforced or 4" reinforced with 6x6x10 gauge wire or fiber mesh. Minimum 5 bag mix.
- <u>Driveways</u>: Minimum 2" stone base. 5" concrete thickness formed with 2"x 6" forms. 6 bag mix reinforced with 6x6x10 wire or fiber mesh.

PAVER BRICKS

• Patios, Walks, Driveways: Minimum 4" compacted stone base.

Maximum Driveway Width from building line to curb:

20' - 1 Car Garage

26' - 2 Car Garage

36' - 3 Car Garage

Concrete Inspections Require Minimum 24 Hour Notice

Inspections may be submitted:

- In person at Development Services Department
- By fax at (708) 403-6215
- On website at www.orland-park.il.us