



DEVELOPMENT SERVICES DEPARTMENT  
14700 RAVINIA AVENUE  
ORLAND PARK, ILLINOIS 60462  
708-403-5300  
FAX 708-403-6215  
[developmentservices@orlandpark.org](mailto:developmentservices@orlandpark.org)  
[www.orlandpark.org](http://www.orlandpark.org)

## **Concrete & Paver Brick Requirements**

### **CONCRETE**

- Patios & Service Walks: Minimum 2” stone base, 4” concrete thickness.
- Public Sidewalks: Minimum 2” stone base. 5” concrete thickness formed with 2” x 6” forms. 6 bag mix reinforced with 6 x 6 x 10 wire or fiber mesh thru driveway.
- Garage Slab: Minimum 2” stone base. 5” concrete thickness reinforced with 6x6x10 gauge wire or fiber mesh. Minimum 6 bag mix.
- Driveways: Minimum 2” stone base. 5” concrete thickness formed with 2”x 6” forms. 6 bag mix reinforced with 6x6x10 wire or fiber mesh.

### **PAVER BRICKS**

- Patios, Walks, Driveways: Minimum 4” of compacted stone base.

Maximum Driveway Width spanning from the building line to the curb:

20’ - 1 Car Garage

26’ - 2 Car Garage

36’ - 3 Car Garage

## **Concrete Inspections Require Minimum 24 Hour Notice**

Inspections require permit#, address, contact information, requested date and time slot and may be submitted:

- In person at Development Services Department
- By fax at (708) 403-6215
- On website at [www.orlandpark.org](http://www.orlandpark.org)
- Email [developmentservices@orlandpark.org](mailto:developmentservices@orlandpark.org)